

~~Patent claims~~

what is claimed is -

1. A method for predicting measurement data until a final time-point using given measurement data, in which:
- a) a stochastic process is matched to the given measurement data;
- b) simulation runs of the stochastic process are carried out from a given time-point until the final time-point;
- c) the forecast measurement data is determined for each simulation run;
- d) measurement data is predicted by stating a range of values, which is determined by the forecast measurement data.
2. The method as claimed in claim 1, in which:
- a confidence range is determined for the prediction of measurement data, where the a% lowest and b% highest forecast measurement data are eliminated.
3. The method as claimed in claim 2, in which:
- a% and b% are equal.
4. The method as claimed in one of the preceding claims, in which:
- the stochastic process is a non-homogeneous Poisson process.
5. The method as claimed in one of the preceding claims, in which:
- the measurement data represents numbers of errors.
6. The method for predicting measurement data using given measurement data, in which:
- a) a stochastic process is matched to the given measurement data;

09868239.080701

Sub
A17

GR 98 P 5929

- 21 -

b) a range is ascertained, by sorting the probability values generated by the

A1
cont'd

09868229.080701

stochastic process according to size, around an expected value;

c) measurement data is predicted within the limits of the range.

5

7. The method as claimed in claim 6, in which: the probability values generated by the stochastic process are sorted symmetrically by size around the expected value.

10

8. An arrangement for predicting measurement data until a final time-point using given measurement data, whereby a processor unit is provided and configured in such a way that:

15

a) a stochastic process can be matched to the given measurement data;

b) simulation runs of the stochastic process can be carried out from a given time-point until the final time-point;

20

c) the forecast measurement data can be determined for each simulation run;

d) measurement data is predicted by stating a range of values, which is determined by the forecast measurement data.

25

9. An arrangement for predicting measurement data using given measurement data, whereby a processor unit is provided and configured in such a way that:

30

a) a stochastic process can be matched to the given measurement data;

b) a range can be ascertained by sorting probability values generated by the stochastic process according to size around an expected value;

35

Sub
A1
cont'd

09858239.080701
T02080"6E289860

GR 98 P 5929

- 23 -

c) the measurement data is predicted within the limits of the range.

Sub
A1
con-
cluded

09868239-080701